

922 SMARTTOUCHLESS HIGH

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Issue date: 03/04/2026

Version: 1.0



SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : 922 SMARTTOUCHLESS HIGH
Product code : SS-922TH-(XX)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Industrial and Institutional High Alkaline Detergent

1.3. Details of the supplier of the safety data sheet

Smart Solutions
12 Corporate Plaza
Suite 150
Newport Beach, CA 92660 - USA
T (949) 431-2732
www.smartsolutions.net

1.4. Emergency telephone number

No additional information available

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Met. Corr. 1 May be corrosive to metals.
Skin Corr. 1 Causes severe skin burns and eye damage.

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US)



GHS05

Signal word (GHS US)

: **Danger**

Hazard statements (GHS US)

: May be corrosive to metals
Causes severe skin burns and eye damage

Precautionary statements (GHS US)

Prevention

: Keep only in original packaging.
Wash hands, forearms and face thoroughly after handling.
Wear protective gloves, protective clothing, eye protection, face protection, and hearing protection.

Response

: If swallowed: rinse mouth. Do NOT induce vomiting.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
If inhaled: Remove person to fresh air and keep comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a poison center or doctor.
Specific treatment (see supplemental first aid instruction on this label).
Take off immediately all contaminated clothing and wash it before reuse.
Absorb spillage to prevent material-damage.

Storage

: Store locked up.

Disposal

: Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Other hazards

No additional information available

922 SMARTTOUCHLESS HIGH

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Sodium xylenesulfonate	(CAS-No.) 1300-72-7	5 – 10	Skin Irrit. 2, H315 Eye Irrit. 2B, H320 STOT SE 3, H335
Sodium hydroxide	(CAS-No.) 1310-73-2	5 – 10	Met. Corr. 1, H290 Skin Corr. 1, H314
UNDECETH-5	(CAS-No.) 34398-01-1	1 – 5	Skin Irrit. 2, H315 Eye Irrit. 2A, H319
butyl glycolether	(CAS-No.) 111-76-2	1 – 3	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Irrit. 2B, H320

Full text of hazard classes and H-statements : see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician.
First-aid measures after skin contact	: Immediately call a poison center or doctor/physician. Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a physician immediately.
First-aid measures after eye contact	: Immediately call a poison center or doctor/physician. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Do NOT induce vomiting. Immediately call a poison center or doctor/physician. Rinse mouth. Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Causes severe skin burns and eye damage.
Symptoms/effects after inhalation	: None under normal conditions.
Symptoms/effects after skin contact	: Burns.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Swallowing a small quantity of this material will result in serious health hazard. Burns.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Sand. Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: No fire hazard.
Explosion hazard	: No direct explosion hazard.
Reactivity	: Thermal decomposition generates : Corrosive vapors.

5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment. Do not enter fire area without proper protective equipment, including respiratory protection.
---------------------------	---

922 SMARTTOUCHLESS HIGH

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.

6.1.1. For non-emergency personnel

- Protective equipment : Wear recommended personal protective equipment.
- Emergency procedures : Ventilate spillage area. Evacuate unnecessary personnel. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".
- Emergency procedures : Ventilate area. Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. See Section 12 for additional Ecological information.

6.3. Methods and material for containment and cleaning up

- For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.
- Methods for cleaning up : Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.
- Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.
- Precautions for safe handling : Ensure good ventilation of the work station. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Avoid contact during pregnancy/while nursing. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray. Wear personal protective equipment.
- Hygiene measures : Wash hands and other exposed skin thoroughly after handling. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Comply with applicable regulations.
- Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Direct sunlight, Heat sources. Keep container closed when not in use. Store in corrosive resistant container with a resistant inner liner. Keep only in original container. Store locked up.
- Incompatible products : Strong acids. Oxidizing agent.
- Incompatible materials : Sources of ignition. Direct sunlight. Metals.
- Packaging materials : Always store product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Sodium hydroxide (1310-73-2)		
ACGIH	ACGIH® TLV® C	2 mg/m³
ACGIH	Remark (ACGIH®)	URT, eye, & skin irr
OSHA	OSHA PEL TWA	2 mg/m³

922 SMARTTOUCHLESS HIGH

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

butyl glycoether (111-76-2)		
ACGIH	ACGIH® TLV® TWA	20 ppm
ACGIH	Remark (ACGIH®)	Eye & URT irr
OSHA	OSHA PEL TWA	240 mg/m³
OSHA	OSHA PEL TWA	50 ppm
UNDECETH-5 (34398-01-1)		
Not applicable		
Sodium xylenesulfonate (1300-72-7)		
Not applicable		

8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: Wear protective gloves.
Eye protection	: Chemical goggles or face shield. Safety glasses.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: Wear appropriate mask.
Environmental exposure controls	: Avoid release to the environment.
Other information	: Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
	: No data available
	: No data available
Odor threshold	: No data available
pH	: 12 – 12.3
pH solution	: 1 %
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 212 °F
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability	: Non flammable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 1.07 – 1.08
Density	: 9.013 lb/gal
Solubility	: Soluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

VOC content	: 7 %
-------------	-------

922 SMARTTOUCHLESS HIGH

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

SECTION 10: Stability and reactivity

10.1. Reactivity

Thermal decomposition generates : Corrosive vapors.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Oxidizing agent. metals.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. Thermal decomposition generates : Corrosive vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

butyl glycolether (111-76-2)	
LD50 oral rat	1746 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg body weight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
LD50 dermal rabbit	435 mg/kg body weight (Rabbit; Experimental value; OECD 402: Acute Dermal Toxicity; 435 mg/kg bodyweight; Rabbit; Weight of evidence; Equivalent or similar to OECD 402)
LC50 Inhalation - Rat	> 4.26 mg/l (4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))
ATE US (oral)	1746 mg/kg body weight
ATE US (dermal)	435 mg/kg body weight
ATE US (gases)	700 ppmV/4h
ATE US (vapors)	3 mg/l/4h
ATE US (dust, mist)	0.5 mg/l/4h
UNDECETH-5 (34398-01-1)	
LD50 oral rat	> 1400 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
Sodium xylenesulfonate (1300-72-7)	
LD50 oral rat	> 7000 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 2000 mg/kg body weight (Equivalent or similar to OECD 402, Rabbit, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 6.41 mg/l (Equivalent or similar to OECD 403, 232 minutes, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s))

Skin corrosion/irritation : Causes severe skin burns.
pH: 12 – 12.3

Serious eye damage/irritation : Assumed to cause serious eye damage
pH: 12 – 12.3

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

butyl glycolether (111-76-2)	
IARC group	3 - Not classifiable

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

922 SMARTTOUCHLESS HIGH

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met. Harmful if swallowed.
Symptoms/effects after inhalation	: None under normal conditions.
Symptoms/effects after skin contact	: Burns.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Swallowing a small quantity of this material will result in serious health hazard. Burns.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Before neutralisation, the product may represent a danger to aquatic organisms.

Sodium hydroxide (1310-73-2)	
LC50 - Fish [1]	189 mg/l (48 h, Leuciscus idus, Fresh water, Experimental value)
EC50 - Crustacea [1]	40 mg/l (48 h, Ceriodaphnia sp., Experimental value, Locomotor effect)
butyl glycolether (111-76-2)	
LC50 - Fish [1]	1474 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	1550 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	≈ 911 mg/l (72 Hr.)
UNDECETH-5 (34398-01-1)	
LC50 - Fish [1]	1 – 10 mg/l (96 hr.)
EC50 - Crustacea [1]	1 – 10 mg/l (48 hr.)
EC50 - Other aquatic organisms [1]	1 – 10 mg/l (96 hr.)(Algae)
Sodium xylenesulfonate (1300-72-7)	
LC50 - Fish [1]	> 1000 mg/l (EPA OTS 797.1400, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value)
EC50 - Crustacea [1]	> 1000 mg/l (EPA OTS 797.1300, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)

12.2. Persistence and degradability

Sodium hydroxide (1310-73-2)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
butyl glycolether (111-76-2)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Photodegradation in the air.
Biochemical oxygen demand (BOD)	0.71 g O ₂ /g substance
Chemical oxygen demand (COD)	2.2 g O ₂ /g substance
ThOD	2.305 g O ₂ /g substance
BOD (% of ThOD)	0.31
Sodium xylenesulfonate (1300-72-7)	
Persistence and degradability	Readily biodegradable in water.

12.3. Bioaccumulative potential

922 SMARTTOUCHLESS HIGH	
Bioaccumulative potential	Not established.
Sodium hydroxide (1310-73-2)	
Bioaccumulative potential	Not bioaccumulative.
butyl glycolether (111-76-2)	
Partition coefficient n-octanol/water (Log Pow)	0.81 (Experimental value; BASF test; 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

922 SMARTTOUCHLESS HIGH

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Sodium xylenesulfonate (1300-72-7)	
Partition coefficient n-octanol/water (Log Pow)	-3.12 (Experimental value, EU Method A.8: Partition Coefficient, 20 °C)
Bioaccumulative potential	Not bioaccumulative.

12.4. Mobility in soil

Sodium hydroxide (1310-73-2)	
Surface tension	No data available in the literature
Ecology - soil	No (test)data on mobility of the substance available.

butyl glycolether (111-76-2)	
Surface tension	0.027 N/m (25 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.451 – 0.882 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

Sodium xylenesulfonate (1300-72-7)	
Surface tension	71 mN/m (20 °C, 90 %, EU Method A.5: Surface tension)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.42 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.
Ecological waste information	: Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT	
Transport document description (DOT)	: UN3266 Corrosive liquid, basic, inorganic, n.o.s. (Sodium hydroxide), 8, III
UN-No. (DOT)	: UN3266
Proper Shipping Name (DOT)	: Corrosive liquid, basic, inorganic, n.o.s. (Sodium hydroxide)
Class (DOT)	: 8 - Class 8 - Corrosive material 49 CFR 173.136
Packing group (DOT)	: III - Minor Danger
Hazard labels (DOT)	: 8 - Corrosive



DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 241
DOT Symbols	: G - Identifies PSN requiring a technical name

922 SMARTTOUCHLESS HIGH

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

DOT Special Provisions (49 CFR 172.102)	: IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 154
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters", 52 - Stow "separated from" acids
Other information	: No supplementary information available.

Transportation of Dangerous Goods

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory		
Acetaldehyde	CAS-No. 75-07-0	< 0.1%
Contains chemical(s) subject to TSCA 12b export notification if product is shipped outside the U.S		
Acetaldehyde	CAS-No. 75-07-0	< 0.1%
Water (7732-18-5)		
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).	
Sodium hydroxide (1310-73-2)		
Not subject to reporting requirements of the United States SARA Section 313		
CERCLA RQ	1000 lb	
butyl glycolether (111-76-2)		
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard	
SARA Section 313 - Emission Reporting	1 %	
ethylene glycol (107-21-1)		
Subject to reporting requirements of United States SARA Section 313		
CERCLA RQ	5000 lb	
SARA Section 313 - Emission Reporting	1 %	

922 SMARTTOUCHLESS HIGH

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Methyl alcohol (67-56-1)	
Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	5000 lb
SARA Section 313 - Emission Reporting	1 %
1,4-dioxane (123-91-1)	
Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	100 lb
SARA Section 313 - Emission Reporting	0.1 %
Ethylene oxide (75-21-8)	
Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	10 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	1000 lb
SARA Section 313 - Emission Reporting	0.1 %
UNDECETH-5 (34398-01-1)	
EPA TSCA Regulatory Flag	FRI - FRI - indicates a polymeric substance containing no free-radical initiator in its Inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used. PMN - PMN - indicates a commenced PMN substance. XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
Acetaldehyde (75-07-0)	
Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	1000 lb
SARA Section 313 - Emission Reporting	0.1 %
2-Propenoic acid, telomer with sodium hydrogen sulfite (66019-18-9)	
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).
Sulfuric acid (7664-93-9)	
Not subject to reporting requirements of the United States SARA Section 313	
Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	1000 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	1000 lb

15.2. International regulations

922 SMARTTOUCHLESS HIGH	
Not listed on the United States TSCA (Toxic Substances Control Act) inventory	
Water (7732-18-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Sodium chloride (7647-14-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Sodium hydroxide (1310-73-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
butyl glycolether (111-76-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
ethylene glycol (107-21-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Listed on EPA Hazardous Air Pollutant (HAPS)	

922 SMARTTOUCHLESS HIGH

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Methyl alcohol (67-56-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on EPA Hazardous Air Pollutant (HAPS)

1,4-dioxane (123-91-1)

Listed on IARC (International Agency for Research on Cancer)
Listed as carcinogen on NTP (National Toxicology Program)
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on EPA Hazardous Air Pollutant (HAPS)

Ethylene oxide (75-21-8)

Listed on IARC (International Agency for Research on Cancer)
Listed as carcinogen on NTP (National Toxicology Program)
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on EPA Hazardous Air Pollutant (HAPS)

UNDECETH-5 (34398-01-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Acetaldehyde (75-07-0)

Listed as carcinogen on NTP (National Toxicology Program)
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on EPA Hazardous Air Pollutant (HAPS)

Sodium sulfate (7757-82-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Sodium xylenesulfonate (1300-72-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

2-Propenoic acid, telomer with sodium hydrogen sulfite (66019-18-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Sulfuric acid (7664-93-9)

Listed as carcinogen on NTP (National Toxicology Program)

Benzenesulfonic acid, C10-16-alkyl derivs. (68584-22-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

15.3. US State regulations

This product can expose you to chemicals including Ethylene oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

ethylene glycol (107-21-1)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	Yes	No	No	

Methyl alcohol (67-56-1)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	Yes	No	No	

1,4-dioxane (123-91-1)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	No	No	No	30 µg/day

922 SMARTTOUCHLESS HIGH

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Ethylene oxide (75-21-8)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	Yes	Yes	Yes	2 µg/day

Acetaldehyde (75-07-0)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	No	No	No	90 µg/day

Sodium hydroxide (1310-73-2)				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List				

butyl glycolether (111-76-2)				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List				

ethylene glycol (107-21-1)				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List				

Methyl alcohol (67-56-1)				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List				

1,4-dioxane (123-91-1)				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List				

Ethylene oxide (75-21-8)				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List				

Acetaldehyde (75-07-0)				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List				

Sodium sulfate (7757-82-6)				
U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List				

Sulfuric acid (7664-93-9)				
U.S. - New Jersey - Right to Know Hazardous Substance List				

SECTION 16: Other information

Other information : None.

Full text of hazard classes and H-statements:

Met. Corr. 1	Corrosive to metals, Category 1
Skin Corr. 1	Skin corrosion/irritation, Category 1

922 SMARTTOUCHLESS HIGH

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)
